

Output Ratings

Generating Set Model	UG14P1/UG16.5E1			
	LPG		Nat Gas	
	Prime	Standby	Prime	Standby
380 – 415V, 50 Hz	14.0 kVA	16.5 kVA	12.5 kVA	15.0 kVA
	11.2 kW	13.2 kW	10.0 kW	12.0 kW
480V, 60 Hz	16.9 kVA	20.0 kVA	16.8 kVA	18.8 kVA
	13.5 kW	16.0 kW	13.4 kW	15.0 kW

Ratings at 0.8 pf

Ratings Definitions

Prime Power – Model UG14P1

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standby Power – Model UG16.5E1

These ratings are applicable for supplying continuous electrical power (at variable load) in event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

Technical Data

Engine Model:	HM 1.8L	
Alternator Model:	LUA1014NX	
Number of Cylinders:	4 in line	
Cubic Capacity: litres (cu.in)	1.8 (111.1)	
Bore/Stroke: mm (in)	84.0 (3.3) / 82.0 (3.2)	
Compression ratio:	8.5:1	
Aspiration:	Natural aspirated	
Frequency:	50 Hz	60 Hz
Engine Speed:	1500 RPM	1800 RPM
Gross Engine Power: kW (hp)	15.7 (21)	19.5 (26)
BMEP: kPA (psi)	691 (100.2)	715 (103.7)
Piston Speed: m/sec (ft/sec)	4.1 (13.5)	4.9 (16.1)
Fuel Consump, UG14P1: LPG m ³ /hr (cfh)	1.9 (67.1)	2.2 (77.7)
Fuel Consump, UG16.5E1: LPG m ³ /hr (cfh)	2.2 (77.7)	2.6 (91.8)
Fuel Consump, UG14P1: NG m ³ /hr (cfh)	4.3 (151.9)	5.6 (197.8)
Fuel Consump, UG16.5E1: NG m ³ /hr (cfh)	5.1 (180.1)	6.3 (222.5)
Heat Rejection to Exhaust System: kW (Btu/min)	TBA	TBA
Heat Rejection to Cooling System: kW (Btu/min)	14.1 (804)	17.1 (970)
Total Radiated Heat: kW (Btu/min)	7.5 (424)	9.0 (512)
Exhaust Temperature: °C (°F)	568 (1054)	600 (1112)
Radiator Cooling Air Flow: m ³ /min (cfm)	63 (2225)	75.6 (2670)
Combustion Air Flow: m ³ /min (cfm)	1.3 (46)	1.6 (57)
Exhaust Gas Flow: m ³ /min (cfm)	3.87 (137)	4.83 (170)

Note: Ratings in accordance with ISO 8528. All engine performance data based on the above mentioned maximum continuous ratings. Fuel Consumption data assumes complete combustion of LPG fuel with a calorific value of 95 MJ/m³ and of Natural gas with a calorific value of 37 MJ/m³.

Dimensions and Weights

Length: mm (in)	Width: mm (in)	Height: mm (in)	Net (+lube oil & coolant): kg (lb)
1350 (53.1)	715 (28.1)	1004 (39.5)	405 (893)

Net = With Lube Oil and Coolant

Generating set pictured may include optional accessories



www.FGWilson.com



UG14P1/UG16.5E1



FG Wilson has manufacturing facilities in the following locations:

Northern Ireland • Brazil • China • India • USA

With headquarters in Northern Ireland, FG Wilson operates through a Global Dealer Network. To contact your local Sales Office please visit the FG Wilson website at www.FGWilson.com

